

5092EX EXPLOSION PROOF SCISSOR LIFT

SPECIFICATIONS

Working Height	56 ft	17.1 m
Raised Platform Height	50 ft	15.2 m
Lowered Platform Height	79 in	2.0 m
Platform Size (inside)	74 x 168 in	1.9 x 4.3 m
Platform Capacity	2000 lbs	907 kg
Overall Width	92 in	2.3 m
Overall Length	176 in	4.5 m
Stowed Height	124.5 in	3.2 m
Deck Extension	5 ft	1.5 m
Ground Clearance (Stowed)	8.0 in	20.3 cm
Ground Clearance (Raised)	0.7 in	1.9 cm
Wheelbase	119 in	3.0 m
Inside Turning Radius	210 in	5.3 m
Outside Turning Radius	301 in	7.7 m
Drive Speed (Stowed)	1 mph	1.6 km/h
Drive Speed (Raised)	0.7 mph	1.0 km/h
Batteries	8 x 6V 420 Amp-hr	
Charger	20 Amp Automatic SCR	

Specifications Subject to Change



SAFETY

- Explosion Proof
- Class I, Division 1, Group D

STANDARD EQUIPMENT

- 50 ft Platform Height
- 56 ft Working Height
- 74 x 168 in Platform Size
- 8.0 in Ground Clearance
- 2000 lb Platform Capacity
- 5 ft Extendable Deck
- 500 lb Extendable Deck Capacity
- Proportional Drive Controls
- Battery Condition Indicator
- Full Height Swing Gate
- Movement Alarm

OPTIONS

- Padded Aircraft Rails
- Enhanced Padded Aircraft Rails
- 3/8" Airline to Platform
- 5 ft Powered Extendable Deck
- Dual 5 ft Roll-out or Powered Extendable Decks
- Remote Mount 600 Amp Charger & Battery