

# 1932EX EXPLOSION PROOF SCISSOR LIFT

## SPECIFICATIONS

Working Height	25 ft	7.6 m
Raised Platform Height	19 ft	5.8 m
Lowered Platform Height	39 in	0.99 m
Platform Size (inside)	26 x 64 in	0.7 x 1.6 m
Platform Capacity	550 lbs	250 kg
Overall Width	32 in	0.81 m
Overall Length	89 in	2.26 m
Stowed Height	80.5 in	1.9 m
Deck Extension	3 ft	0.91 m
Ground Clearance (Stowed)	2.375 in	6 cm
Ground Clearance (Raised)	0.7 in	1.8 cm
Wheelbase	55 in	1.4 m
Inside Turning Radius	Zero	
Outside Turning Radius	66 in	1.7 m
Drive Speed (Stowed)	1 mph	1.6 km/h
Drive Speed (Raised)	0.7 mph	1.1 km/h
Batteries	4 x 6V 250 Amp-hr	
Charger	20 Amp Automatic SCR	

Specifications Subject to Change



## SAFETY

- Explosion Proof
- Factory Mutual Approved
- Class I, Division 1, Group D

## STANDARD EQUIPMENT

- 19 ft Platform Height
- 25 ft Working Height
- 26 x 64 in Platform Size
- 2.375 in Ground Clearance
- 550 lb Platform Capacity
- 3 ft Extendable Deck
- 250 lb Extendable Deck Capacity
- Proportional Drive Controls
- Battery Condition Indicator
- 250 Amp Hr Battery
- Full Height Swing Gate
- Movement Alarm

## OPTIONS

- Padded Aircraft Rails
- Enhanced Padded Aircraft Rails
- 3/8" Airline to Platform