

E X S e r i e s

Class I, Division 1, Hazardous Environment

T66JEX



	T66JEX	
Specifications	US	Metric
Platform Height	66 ft	20.62 m
Platform Capacity	500 lb	227 kg
Platform Size	36 x 96 in	.91 x 2.44 m
Stowed Height	8 ft 5 in	2.57 m
Stowed Length	33 ft 6 in	10.21 m
Horizontal Reach	56 ft 9 in	17.3 m
Overall Width	7 ft 11 in	2.41 m
Tail Swing	3 ft 9 in	1.14 m
Outside Turning Radius	11 ft 4 in	3.45 m
Inside Turning Radius	17 ft 9 in	5.4 m
Ground Clearance	12. in	30 cm
Platform Rotation	180° Hydraulic	
Jib Range of Articulation	6 ft, 132°	1.83, (+71,-61)
Travel Speed	0.5 mph/2.5 mph	0.8 kph/4 kph
Wheel Base	7 ft 8 in	2.34 m
Gross Weight (est)	28,000 lbs	12,701 kg
Gradeability 2WD	20%	20%
Power Source	48vdc 600 amp-hr Battery	

Specifications Subject to Change Without Prior Notice

STANDARD EQUIPMENT:

- 66 ft Platform Height
- 72 ft Working Height
- Horizontal Outreach 56 ft 9 6 in
- Platform Size 36 x 96 in
- Overall Width 7 ft 11 in
- Stowed Height 8 ft 5 in
- Stowed Length 33 ft 6 in
- Ground Clearance 12. in
- Proportional Hydraulic Controls
- 48 VDC 600 Amp-Hr Battery
- 6 ft. (1.83m) Articulating Jib



**This Machine is Factory Mutual
Approved for Class I Div 1 Group D**

MLE
MAN & MATERIAL LIFT ENGINEERING
5707 S. Pennsylvania Avenue
Cudahy, WI 53110
Phone: 414-486-1760
Fax: 414-486-1763
www.manliftengineering.com
sales@manliftengineering.com